

F60 FILM DEVELOPER

Fine Grain Developer

F60 FILM DEVELOPER is an extremely fine grain, phenidone based developer for all films, especially Kodak's TMAX films.

F60 FILM DEVELOPER can be used at dilutions from 1+4 to the recommended dilution of 1+9 for normal contrast; and can be diluted further to 1+19 for push processing.

F60 FILM DEVELOPER exhibits excellent control characteristics.

F60 FILM DEVELOPER is ideal for automatic machine processing, replenished with working solution, prepared by diluting concentrate 1+4, at the rate of 0.4 ml/sq.in. film.

Suggested starting points for film developing times:

	68°F @ 1+9 Normal Dev.	75°F @ 1+9 Normal Dev.	75°F @ 1+19 Pushed Dev.
Kodak T-MAX 100	7 min	6 min	12 min
Kodak T-MAX 400	8 min	7 min	12½ min
Kodak TRI-X Pan	6 min	5½ min	11 min
Kodak PLUS-X Pan	5½ min	5 min	9 min
Agfapan APX 100	9 min	6½ min	12½ min
Agfapan APX 400	8 min	6 min	12 min
Ilford FP4	5½ min	5 min	9 min
Ilford HP5	7 min	6 min	12 min
Fuji Neopan 400	6 min	5½ min	11 min

CATALOG NUMBER

11 0114
11 0117
11 0128

PACKAGE

12x 32 ounces
4x 1 Gallon
5 Gallons